

NKB5000

HD Network Control Keyboard



Features :

- Keyboard to Control
 - DAHUA Standalone DVR
 - DAHUA (Network) High Speed Dome
 - DAHUA High Speed Dome
 - Central Management Platform
 - Network Video Server
- RS232, RS485 & Network Connections(Wifi)
- Four Dimensional Joystick Control of PTZ Functions
- Support 4K live view; Support HDMI & VGA sync output
- Support snapshot and recording to U-disk
- Support Video-Wall display
- Support bidirectional talk
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control
- Auxiliary Functions, OSD and operation guides Control



Technical Specification

Model

Model	NKB5000
-------	---------

System

Main Processor	Dual-core Braswell Processor
Operation System	Embedded LINUX 4.2.0

Audio&Alarm

Audio Input/Output	1 pair 3.5mm jack, support bidirectional talk
Loudspeaker	1
Alarm In	4, High-low level
Alarm Out	4 (3 relay, 1 12V_1A)

Display

Stream Type	H.265, H.264, MPEG, Nonstandard
Resolution	5CH@4K/16CH@1080P
Display split	1/4/8/9/16
Screen	10.1" TFT LCD touch screen (1280*800)

General

Keyboard Panel	Electromechanical
Joystick	4-axis(zoom, focus, iris)

Control	Output Control	Support video-wall display HDMI output	
	Control Mode	Direct Mode	Interface: 2 RS232/ 1 RS485/1 RS422 DVR Protocol: DH-2 Dome Protocol: DH-SD1/PELCO-D/PELCO-P, etc
		Network Mode	Interface: RJ45(2 RJ-45 port (10/100/1000M)) / Wi-Fi DVR/ Network Dome: IP Address/Port/Protocol
Max Remote Users		20 (each can manage up to 256 unit devices)	
USB Interface		2 USB3.0 + 2 USB2.0	

Environmental

Power Supply	DC12V, 4A
Power Consumption	5W
Working Temperature	-10°C ~+55°C
Working Humidity	10%~95%
Atmosphere Pressure	86kpa~106kpa
Dimension	Host: 425mmx193.6mmx53.61mm (WxDxH) (height: exclude joystick) Mini Keyboard: 420.97mmx105mmx19.7mm (WxDxH)
Weight	<2KG (exclude package)