

DHI-HY-A0321-CTXF

Addressable Manual Call Point



- Convenient wiring: Two-wire, polarity-free
- Reliable communication: Built-in microprocessor, performance is stable
- Ultra-low power consumption: Ultra-low monitoring current and alarm current
- Independent output: A pair of normally open contacts
- Simple installation: With a plug-in structure, easy to install and construct
- Prevent accidental touch: Features a transparent cover to prevent fire alarm caused by accidental touch
- Designed in accordance with EN54-11 standard

System Overview

DHI-HY-A0321-CTXF Addressable Manual Call Point is a mated product of the Addressable Fire Alarm Control Panel, pressing the manual call point to send alarm signals to the panel.

Functions

Fast response

When there is a fire alarm, manually press the button, the alarm signal is sent to the control panel within 1 second.

Normally open contact

Features a pair of normally open contacts, providing an activation signal to other devices.

Scene

It is suitable for residential and industrial buildings such as hotels, shopping malls, hospitals, office buildings, schools, banks, libraries, factories, and warehouses.

Technical Specification

Electrical

Working Voltage	DC24V
Current	Monitoring current: ≤ 350μA Alarm current: ≤ 400μA
Contacts Capacity	DC30V/100mA
Indicator	Fire Alarm Red indicator flashes slowly during polling, flashes quickly during malfunction and remains lit during alarm Phone Red indicator flashes during polling and communication

Communication

Wiring	Two-wire, polarity-free
Addressing Method	Electrical encoder
Address Range	1–254
Communication Distance	1500 m (4921.26 ft)


Environment

Operating Temperature	-10°C to +55°C (+14°F to +131°F)
Storage Temperature	-20°C to +65°C (-4°F to +149°F)
Operating Humidity	≤ 95% RH (no condensation)


Construction

Color	Red
Dimensions (with base)	90 mm × 90 mm × 44 mm (3.54" × 3.54" × 1.73")
Weight (with base)	136 g (0.30 lb)
Compliance Standard	EN54-11 (applying)

Installation



Dimensions (mm/inch)



Ordering Information

Type	Model	Description
Addressable Manual Call Point	DHI-HY-A0321-CTXF	Addressable Manual Call Point
Accessories	DHI-HY-ANDZ	Manual Call Point Base