

ALARM-D201MC-WE Wireless Magnetic Contact



This is a wireless opening detector that notifies of first signs of room intrusion by means of a broken door or window.

- Simple and elegant appearance design
- Frequency hopping against jamming for reliable transmission

▪ Specification

Communication	
Transmission technology	868.0-868.6 MHz
Transmission range (free space)	Up to 1,600 m
Maximum effective radiated power (ERP)	25 mW max
Radio signal modulation	2GFSK
Detection performance	
Detection method	Opening Contact
Detection gap	25 mm max
Software features	
Temperature indicator	Yes
Indication	
Indication method	LED
Electrical characteristics	
Power supply	1 × AA battery
Power consumption	max current: 140 mA quiescent current: 1 uA
Battery life	Up to 2 years (standby time)
General	
Dimension (W×H×D)	24 x 104 x 23.5 mm 14.4 x 50.0 x 17.5 mm
Weight	49 g
Operation temperature	-10 °C to 55 °C (14 °F to 131 °F)
Operation humidity	10% to 90%

▪ Available Model

ALARM-D201MC-WE



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
Technical Support: support@hikvision.com

Follow us on social media to get the latest product and solution information.

