



FEATURES:

- **Construction:**

The stainless steel wall mounting enclosures are specially suitable for corrosive environments and installations where hygiene is essential. Also in chemical and food industries, etc.

- Monobloc watertight 304 or 316 stainless steel enclosures.

- **Door:**

Doors open up to 120° , can be hinged right or left and it's easily removed with lift-of type spring pin hinges. The gasket is continuous formed polyurethane which provides excellent sealing and a high IP rating over a very long life.

- **Gland Plates:**

Gland plates made of SS304/SS316 are provided with gaskets and fixing studs.

- **Finish:**

Scotch brite (AST) type mechanical polish for an excellent surface quality and improve protection against corrosion.

KEY ATTRIBUTES:

Product Name	Stainless steel 316 wall mounted enclosure
Model	BJSS
Supply Include	Enclosure and door, galvanized mounting plate, lock system, gland plate, sealing gasket and accessories, metal brackets not include in standard supply
Surface Treatment	Electrical polish
Height	200 — 1200 mm
Width	200 — 1200 mm
Depth	150 — 500 mm
Thickness	1) Height \leq 800 mm: Door and body 1.2 mm, mounting plate 1.5 mm 2) Height $>$ 800 mm: Door and body 1.5 mm, mounting plate 2.0 mm
Door Type	Width \leq 1000 mm Single door Width $>$ 1000 mm Double door
Lock Type	BJLK-005



PRODUCT CAPABILITY:

Waterproof	IP66
Impact Resistance	IK10
Maximum Opening Angle	Reversibility 120°
Certification	CE, TUV, IEC