

# VDO2004L-WP

IP & Wi-Fi Villa Indoor Monitor



- 4.3" TFT capacitive touchscreen.
- Unlock the door.
- Set DND period.
- IPC surveillance.
- 4-channel alarm input and 1-channel alarm output.
- Supports standard PoE.
- Ethernet and Wi-Fi.



## Technical Specification

System	
Main Processor	Embedded Processor
Operating System	Embedded Linux OS
Network Protocol	UDP; TCP; IPv4; RTSP; SIP; RTP
Basic	
Screen Type	Capacitive Touchscreen
Display Screen	4.3" TFT display
Screen Resolution	480 (H) × 272 (V)
Audio Compression	G.711A; G.711U; PCM
Audio Input	1 channel
Audio Output	1 built-in speaker and 1 receiver speaker
Audio Mode	Two-way audio
Audio Enhancement	Echo suppression/digital noise reduction
Audio Bit Rate	16 kHz, 16 bit
Function	
Communication Mode	Full digital
Information Release	Text messages can be received and viewed on the indoor monitor
Elevator Control	You can control the elevator through the indoor monitor
DND Mode	Do not disturb period can be set.
Number of Extensions	Apartment: 4; Villa: 9
Alarm Output	1
Network Port	1 × RJ-45 10/100 M self-adaptive Ethernet port
Performance	
Casing Material	ABS

## General

Appearance Color	White
Power Supply	12 VDC, 1 A; standard PoE (IEEE 802.3af/at)
Power Adapter	Not included
Installation	Surface mount
Accessory	Surface mount bracket, alarm ribbon cable, and power-supply pins are provided
Product Dimensions	136.0 mm × 140.0 mm × 25.5 mm (5.35" × 5.51" × 1.00")
Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Operating Humidity	10%–95% (RH), non-condensing
Power Consumption	≤4 W (standby); ≤6 W (working)
Gross Weight	0.21 kg (0.46 lb)

## Dimensions (mm[inch])

