



## FEATURES:

- **Construction:**

Fully welded, The front lip of the enclosure is folded to provide rigidity and forms a gutter to keep liquids from the gasket.

Four wall mounting holes on the back panel of the enclosure.

- **Door:**

Folded edges provide rigidity to the door, Doors open up to 120° , can be hinged right or left and it's easily removed with lift-of type spring pin hinges.

The gasket is continuous formed polyurethane which provides excellent sealing and a high IP rating over a very long life.

Doors are provided with standard locks.

- **Gland Plates:**

Gland plates are provided with gaskets and fixing studs.

- **Finish:**

Epoxy polyester powder coated with RAL7035 or RAL7032.

## KEY ATTRIBUTES:

---

<b>Product Name</b>	Wall mounted enclosure
<b>Model</b>	BJS1
<b>Supply Include</b>	Enclosure and door, mounting plate, lock system, gland plate, sealing gasket and accessories, metal brackets not include in standard supply
<b>Powder Coating</b>	RAL7035
<b>Height</b>	200 — 1200 mm
<b>Width</b>	200 — 1200 mm
<b>Depth</b>	150 — 500 mm
<b>Thickness</b>	1) Height < 600 mm: Door and body 1.2mm, mounting plate 1.5 mm 2) 600 mm < Height ≤ 800 mm: Door 1.5mm, body 1.2 mm, mounting plate 1.5 mm 3) Height ≥ 1000 mm: Door and body 1.5 mm, mounting plate 2.0 mm
<b>Door Type</b>	Width ≤ 1000 mm Single door Width > 1000 mm Double door
<b>Lock Type</b>	BJLK-002

## PRODUCT CAPABILITY:

---

<b>Waterproof</b>	IP66
<b>Impact Resistance</b>	IK10
<b>Maximum Opening Angle</b>	Reversibility 120°
<b>Paint Finish</b>	Epoxy Polyester Coating
<b>Certification</b>	CE, TUV, IEC